Product Catalogue





W+S GmbH Lackchemie und Aerosol-Technik



We do more than corrosion protection!

W+S Aerosols

WS-Zink®-Products	06
Varnishes	07
Cleaner	09
Technical Sprays & Maintenance Products	10
Primers	11
WS-Plast [®]	12
Equipment	12

W+S Varnishes

WS-Plast [®]	13
WS-Zink [®]	17
WS-Anti-Zinc Paste	19
1-K Basecoats	21
2-K Basecoats	23
1-K Topcoats	25
2-K Topcoats	29
Cleaners & Maintenance Products	33
Dilutions & Hardeners	37
Equipment	41



W+S GmbH Lackchemie & Aerosol-Technik is a medium sized independent company based in Karlstein, lower Franconia. It was founded in 1980 with the aim to produce and sell high quality corrosion protection and zinc coating products. The company started with two products: WS-Zink 80/81 – a high quality zinc repair paint and WS-Plast thick layer coating M 4200 – which is especially suitable for the coating of galvanized surfaces. Both products are still the major brands and top sellers of our company.

In 1996, the company moved to the present location Karlstein am Main. This movement and expansion were enabled by rising customer demands and an increasing product range.

Therefore, it was decided to improve different products like WS-Plast[®], WS-Zink[®] 80/81 and Galvanal[®] in the same year. From now on, they should also be available as aerosols.

To meet customers' requirements and to be able to continue an independent production, the company invested in a fully automatical filling machine for aerosols. It realizes the single steps – filling – closing – gassing – marking and labelling – in a completely automatical way and ensures a constant high quality of our products.

The modern and efficient filling and production machine enabled W+S GmbH to become active as a contract filler and establish in this field in the following years.

With a product range of more than 250 different articles, today W+S GmbH is one of the leading companies in zinc coatings and corrosion protection.

The company has 30 employees, who do not only provide an excellent customer service, but also produce approx. 500 tons of lacquer and 2.5 million spray tins a year.

WS-Aerosols





WS-Zink®-Products **Recovery of damaged areas** in the hot dip galvanizing

WS-Zink® 22-01

Zinc like shine

High zinc-containing zinc/aluminum spray for the repair of damaged areas on hot-dip galvanized parts, with suitability test according to DIN EN ISO 1461 from an independent testing institute.

Container size: 400 ml Item No. 77413221

WS-Zink® 80/81

Zinc like shine

With WS-Zink® Spray 80/81 it is possible to reach 120 µm layer thickness on vertical surfaces with one operation. Corresponds to DIN EN ISO 1461. WS-Zink® 80/81 is excellently corrosion-resistant against atmospheric influences. The outstanding protective effect is based on the electrochemical behavior of the metallic zinc dust, which first oxidizes in an aggressive atmosphere due to its less noble structure compared to iron, and then effectively protects the underlying iron structure.

Container size: 400 ml Item No. 77413999

WS-Zink® PURE 900

zinc grey

WS-Zink® PUR 900 is an active corrosion protection spray with particularly good conductivity during spot welding and can be recoated well with commercially available paints. Corresponds to DIN EN ISO 1461. The corrosion protection depends on the chosen quality of surface pretreatment. It should be as metallic pure as possible in accordance with EN ISO 8501.

Container size: 400 ml Item No. 77413900

WS-Zink® Repair 108

silver

WS-Zink® Repair 108 is a high-quality, heat-resistant corrosion coating for the repairing of hot-dip galvanized parts. Furthermore, it is used in air conditioning, refrigeration and ventilation technology, in vehicle and body construction and in metal construction as a well-covering metal coating. The product adheres well to steel, zinc, non-ferrous metals and plastics.

Container size: 400 ml Item No. 77413108



Galvanal®

silver, metallic reflecting

Galvanal® is a glossy liquid aluminum spray for use on car rims, exhaust systems, aluminum components, galvanized surfaces, air conditioning, refrigeration and ventilation systems, vehicle bodies, heat-stressed equipment and housings, for the visual enhancement of zinc and zinc dust coatings.

Container size: 400 ml Item No. 77413888

Galvanal® Cristall

silver shinina

Galvanal® Cristall is a liquid aluminum spray for use on car rims, exhaust systems, aluminum components, galvanized surfaces, air conditioning, refrigeration and ventilation systems, vehicle bodies, heat-stressed devices and housings. For the visual improvement of zinc and zinc dust coatings, etc. The product is characterized by its high abrasion resistance.

Container size: 400 ml Item No. 77413800

WS-Nirosta

Metallic shiny

WS-Nirosta provides all metals a metallic scratch and weather-resistant surface finish. The adhesion is also guaranteed on wood, cardboard, stone and many plastics. WS-Nirosta behaves electrochemically neutral on chromium-nickel steels, therefore you can often abstain from chemical pickling at subordinate sites.

Container size: 400 ml Item No. 77413200



WS-Silone Thermal Paint black mat	WS-Clearcoat high gloss
WS-Silan is a high quality special varnish with a guaranteed heat resistance of up to 800 ° C. The product has anti-corrosion properties. Suitable for temperature-stressed steel items such as exhausts, stoves, grills, etc.	WS-Clearcoat is a high-quality, colorless 1-component coating varnish, especially for 2-layer metallic finishes. The spray is not yellowing, is fast drying and weather resistant.
Container size: 400 ml Item No.77413464	Container size: 400 ml
WS-Acrylic Paint Spray	WS-Synthetic Revin Paint Spray high gloss
	WS-Synthetic Revin Paint Spray high gloss WS-Synthetic resin paint spray is a glossy quality synthetic resin paint for trade and hobby. Excellent adhesion to almost all materials. Suitable for inside and outside.

We stir the acrylic and synthetic resin paint spraysfor you in all RAL colors. The minimum purchase per color is a box of 12 tins.



WS-Rust Remover

WS-150 Cold Degreaser

not attack metal parts.

WS-Rust Remover dissolves stuck and corroded connections of screws, bolts, locks and hinges, through its excellent creeping capacity. A further rusting is prevented. Due to the simultaneous lubricating effect creaking and squeaking is prevented and protection against further wearing is given.

Container size: 400 ml Item No. 77413630

WS-160 Cold Degreaser

WS-160 Cold Degreaser cleans smooth, firm surfaces of grease and pigment soiling as well as adhesive residues and printing inks. Easily removes paper labels and residues of pressure-sensitive adhesives. Suitable for plastic, stainless steel or glass surfaces. Does not attack metal parts and painted surfaces.

Container size: 400 ml Item No. 77413516

WS-Paint-Re*s*idue-Remover

WS-Paint-Residue-Remover works reliably with commercially available one- and two-component paints. Paint residues can be easily removed with a spatula after a short exposure time. Contains no CHC (methylene chloride).

Container size: 400 ml Item No. 77413012

Container size: 400 ml Item No. 77413515

WS-150 Cold Degreaser cleans oily and greasy sheets, profiles, light

metal, plastic and rubber parts. Also removes mold release agents, does

WS-Spray-Cleaner

WS-Spray-Cleaner is a residue-free cleaner, especially for the cleaning of brake systems, clutches and engine systems. Dissolves resin and adhesions of old lubricants and oils.

Container size: 400 ml Item No. 77413634



WS-40 Multifunctional Oil

The WS-40 Multifunktionsoil forms a hardly greasing lubrication film, sucks into the smallest pores, cleans, dissolves resinified lubricants, displaces water, is antistatic and protects against moisture and corrosion. Universal lubricant for precision mechanics, electronics, mold making, automotive mechanics, industrial and model making.

Container size: 400 ml Item No.77413600

WS-Silicone/pray _

WS Siliconespray is a high-quality liquid lubricant that leaves a permanent lubricating film on plastic, metal or rubber surfaces. It enters deeply into porous surfaces and impregnates even work clothes and work gloves. As an anti-adhesive agent, it reliably prevents the sticking of sticky media.

Container size: 400 ml Item No. 77413250

WS-Stainless Steel Care Spray

WS-Stainless Steel Care Spray cleans and maintains matt and polished stainless steel surfaces. Contaminants such as grease, oil and finger marks are easier to remove. The spray leaves a wafer-thin care film that counteracts re-polluting.

Container size: 400 ml Item No. 77413638

WS-Teflon/pray

WS-Teflonspray is manufactured on the basis of finest PTFE waxes. Particle size: less than 3 μ m acc. AST MB 330. Coefficient of friction: 0.1 Temperature resistant from -240 ° C to 260 ° C. Softens from 315 ° C, does not melt. Therefore it is an indispensable and reliable lubricant and release agent in mold and plastic construction and fine tool manufacturing.

Container size: 400 ml Item No. 77413633

WS-Releasespray TST 401

WS-Releasespray TST 401 is a silicone-free release agent for welding technology and plastics processing based on natural oils. Prevents adhesion of welding beads. Also usable as nozzle protection spray. Has a good separating and cleansing effect.

Container size: 400 ml Item No. 77419030



WS-Korrogrund®

grey

WS-Korrogrund® primer spray in the colors gray and maroon, is a fastdrying corrosion protection primer with excellent passivating effect. Recoatable with all 1K topcoats based on synthetic resin (alkyd resin). For other 1K paints, a sample coating is recommended in case of doubt. WS-Korrogrund® can be used on all steel, iron and cast parts indoors and outdoors. The product is ideal for all applications of locksmithing, metal or steel construction, plant and mechanical engineering, container construction, etc. and is resistant to cold and tropical temperatures.

Container size: 400 ml Item No. 77413072

WS-Korrogrund®

maroon _

WS-Korrogrund® primer spray in the colors gray and maroon, is a fastdrying corrosion protection primer with excellent passivating effect. Recoatable with all 1K topcoats based on synthetic resin (alkyd resin). For other 1K paints, a sample coating is recommended in case of doubt. WS-Korrogrund® can be used on all steel, iron and cast parts indoors and outdoors. The product is ideal for all applications of locksmithing, metal or steel construction, plant and mechanical engineering, container construction, etc. and is resistant to cold and tropical temperatures.

Container size: 400 ml Item No. 77413112

WS-Plast® Thickfilm M 4200

silky mat

Original $\textbf{WS-Plack}^{\$}$ spray can to repair damaged areas due to transport or installation. Smaller zinc coatings can be done directly on site.

Container size: 400 ml

Available Colors:

0001 smithy black	Item No. 77410001
0003 graphit EG	Item No. 77410003
0008 black mica	
0021 brillant-black	Item No. 77410021
DB 703 grey	Item No. 77413073
RAL6005mossgreen	
RAL7016anthracite	
RAL 7030 stone grey	
RAL9010pure white	





WS-Sprayboy

Spray tower

The optimal help for a uniform application from the spray can.

..... Item No. 9860724

WS-Plast®

Resistant protective coating in duplex system



WS-Plast® Thickfilm M 4200

silkmat

WS-Plast® Thick Film M 4200 is a pure acrylate paint system which, due to its special composition, adheres to zinc and aluminum surfaces without any primer. It is suitable for use as a duplex system (hot dip galvanizing plus coating) depending on the layer thickness and the ambient conditions for coating acc. to EN ISO 12944. It is also suitable for coatings of hot-dip galvanized enclosures, gates, balcony railings, lamps, gutters, steel structures, blacksmithing, as well as non-anodized aluminum components such as porches, flagpoles, cladding, etc. Always electrostatically adjusted. WS-Plast® thick film M 4200 can be rolled, sprayed or painted.

	Container	size:	750	ml
--	-----------	-------	-----	----

0001 black wrought iron	Item No. 10110001
RAL 6005 mossgreen	Item No. 10116005
RAL 9010 pure white	Item No. 10119010

Container size: 2,5 l

0001 black wrought iron	Item No. 10210001
0002 eloxal brown	Item No. 10210002
RAL 1013 perl white	Item No. 10211013
RAL 6005 moss green	Item No. 10216005
RAL 7001 silver grey	
RAL 7016 anthracite	Item No. 10217016
RAL 8017 chocolate brown	Item No. 10218017
RAL 9002 grey white	Item No. 10219002
RAL 9010 pure white	Item No. 10219010
RAL 9016 traffic white	

Container size: 11 kg

Item No. 10310001
Item No. 10310002
Item No. 10311013
Item No. 10316005
Item No. 10317001
Item No. 10317016
Item No. 10318017
Item No. 10319002
Item No. 10319010
Item No. 10319016

Container size: 30 kg

0001 black wrought iron	. Item No. 10410001
0002 eloxal brown	. Item No. 10410002
RAL 1013 perl white	Item No. 10411013
RAL 6005 moss green	. Item No. 10416005
RAL 7001 silver grey	. Item No. 10417001
RAL 7016 anthracite	. Item No. 10417016
RAL 8017 chocolate brown	. Item No. 10418017
RAL 9002 grey white	. Item No. 10419002
RAL 9010 pure white	. Item No. 10419010
RAL 9016 traffic white	. Item No. 10419016

<u>Required dilution for WS-Plast[®] and WS-Plast[®] EG</u>	
WS-Plast® Dilution MV 751	see page 16



W.





<u>Special Colors:</u>

Special Colors can be mixed according to RAL standard. Due to production reasons special colors are only produced in 2.5 I cans, 11 kg buckets or 30 kg Hobbock.



WS-Plast® Thickfilm M 4200 EG

silkmat

Container size: 750 ml	
0003 graphite EG	Item No. 10110003
0004 silver (RAL 9006)	Item No. 10110004
0005 copper	Item No. 10110005
0007 old copper	Item No. 10110007
0008 black mica	

Container size: 2,5 L

Container Size: 2,5 L	
0003 graphite EG	Item No. 10210003
0004 silver (RAL 9006)	Item No. 10210004
0005 copper	Item No. 10210005
0007 antique copper	Item No. 10210007
0008 black mica	
0010 steel mica	Item No. 10210010
0017 azure mica	Item No. 10210017
0018 emerald mica	
0019 amber mica	
0020 stainless steel satin *	
0021 brilliant-black EG	
0023 nobel– rust bright	
0024 nobel rust dark	Item No 10210024
RAL 9007 grey aluminium	Item No. 102190021
DB 701 silver grey	
DB 702 grey	Item No. 10210702
DB 703 grey	Item No. 10210703
DB 704 grey	Item No. 10210704
5 J 1	

Container size: 11 kg	
0	Itom No. 10210002
0003 graphite EG	
0004 silver (RAL 9006)	
0005 copper	Item No. 10310005
0007 antique copper	Item No. 10310007
0008 black mica	Item No. 10310008
0009 black metallic	Item No. 10310009
0010 steel mica	Item No. 10310010
0017 azure mica	Item No. 10310017
0018 emerald mica	Item No. 10310018
0019 amber mica	Item No. 10310019
0020 stainless steel satin *	Item No. 10310020
0021 brilliant-black EG	Item No. 10310021
0023 noble rust bright	Item No. 10310023
0024 mobel rust dark	
RAL 9007 grey aluminium	Item No. 10319007
DB 701 silver grey	Item No. 10310701
DB 702 grey	Item No. 10310702
DB 703 grey	Item No. 10310703
DB 704 grey	Item No. 10310704
• •	

Container size: 30 kg	
0003 graphite EG	Item No. 10410003
0004 silver (RAL 9006)	
0005 copper	Item No. 10410005
0007 antique copper	
0008 black mica	
0009 black metallic	Item No. 10410009

Further DB colors on request.











*Due to technical reasons this color ist not electrostatically adjusted

WS-Patina

silkmat

WS-Patina is an effective spot color for wrought-iron work on pure acrylate basis. It is suitable for indoor and outdoor use. WS-Patina is used for optical change of e.g. stair railings, garden gates, candlesticks, signs, lanterns, bars, lamps. There is no need for subsequent sealing.

Container	size:	250	ml

0011 patina green	Item No. 16110011
0012 patina copper	
0013 patina silver	
0014 patina gold	
0015 patina purple	
0016 patina gold bronze	

Container size: 11 kg Eimer (auf Anfrage)

0011 patina green	Item No. 16310011
0012 patina copper	Item No. 16310012
0013 patina silver	Item No. 16310013
0014 patina gold	Item No. 16310014
0016 patina gold bronze	

Required dilution:

ws-Plark® Dilution MV 751	Al anen aoz
	see paye to

WS-Plast® Brush Paint K 3706

satin glossy_

Thick-coat single-coat paint predominantly for painting and rolling on galvanized steel and aluminum with active corrosion protection, low solvent content. Specially developed for small parts and repairs. Available in RAL and NCS shades acc. to color group table.

Container size:

3 kg	Item No. 10513706

<u>Required dilution:</u>	
WS-PUR Dillution UV 150	see page 40





ພຽ-Plart® Dilution MV 751

		WS-Plazt®-Thickfilm und WS-Patina.	м	4200	(and	EG),
	iner size:			14.		110751
101				Ite	em No. 18	410751
30 I				Ite	em No. 18	510751





Restore damaged areas in the hot dip galvanizing



WS-Zink® 80/81

zinc-like shine

The proven high-zinc repair paint for hot-dip galvanized components of all kinds, with more than 90% metallic zinc dust in the pigment, according to DIN EN ISO 1461. WS-Zink® 80/81 is pasty, due to that you can achieve a high film thicknesses in one operation. WS-Zink® 80/81 is spreadable ready.

Container size:	
100 ml	
250 ml	Item No. 1121808
500 ml	Item No. 1131808
1000 ml	Item No. 1141808
18 kg	Item No. 1151808

nequirea Bhadon.	
WS-Nitro-Universal-Dilution ZV 559 see pa	ıge 39

WS-Zink® PUR 2000

Zinc like shine

One-component moisture-curing polyurethane zinc dust coating in accordance with DIN ISO EN 1461. Also complies with the German supplement to this standard. Zinc similar shining. The product must be fully processed after opening.

Container size:	
100 ml	em No. 11112000
250 ml Ite	em No. 11212000

WS-Zink® A 6005

grey

1 component zinc dust primer. WS-Zink® A 6005 has approx. 95% pure zinc dust in dry film. When the surface has been sandblasted first, it is particularly suitable for heavy corrosion protection.

Container size: 1000 ml 2,5 l 25 kg	Item No. 11216005
<u>Required Dilution:</u> WS-Nitro -Universal-Dilution ZV 559	see page 39

WS-Zink® Repair Paint 108

silver

Container size: 250 ml

500 ml ..

WF-Zink® Repair Paint 108 is a zinc / aluminum paint, suitable for repairing galvanized components on the building site or in the workshop. The epoxy resin ester binder in combination with metallic zinc and aluminum pigmentation ensures good corrosion protection even in an aggressive atmosphere. The adhesion to iron or zinc -surfaces is good.

1000 ml Item No. 11310108

WS-Zink Automotion 10 1 1 the state of the state state of the state of the state state of the state of the state state of the state of the state of the state state of the state of t

. Item No. 11110108







WS-Anti-Zinc-Paste



WS-Anti-Zinc Paste

grey

WS-Anti-Zinc Paste is a coating material for the coating of steel parts that need to stay zinc-free during hot-dip galvanizing. WS-Anti-Zink Paste is pasty, acidresistant and heat-resistant due to specially selected pigments and fillers. The material is ready for brushing and is also ideal for thick-walled components with a longer residence time in the zinc bath. A second coat also reliably protects threaded bolts. In addition, a sharp demarcation of the areas to be covered without infiltration is possible.

Container size: 250 ml Item No. 11112012

1000 ml Item No. 11212012

7,5 kg Item No. 11312012







I-K Basecoats



WS-Korrogrund®

grey or maroon ____

Fast-drying, high-quality corrosion protection primer with active pigments, free of lead and chromate, rich, mild in odour, electrostatically adjusted.

Container size: 2,5 l	Container size: 12,5 kg
grey Item No. 12113526	grey Item No. 12213526
maroon Item No. 12113601	maroon Item No. 12213601
Container size: 35 kg	Required dilution for WS-Korrogrund®:

Container Size. JJ ky	
grey	Item No. 12313526
maroon	

<u>Required dilution for WS-Korrogrund</u> ®:	
WS-Plast® Dilution MV 751	see page 16
Resin dilution KV 657	see page 39



WS-Korrogrund® MIX

Quick-drying, high-quality zinc phosphate corrosion protection primer in RAL standard colors, electrostatically adjusted.

Standard colors:

Container size: 12,5 kg	
ca. RAL 5012 light blue	Item No. 12215012
ca. RAL 6011 reseda green	Item No. 12216011
ca. RAL 7035 light grey	Item No. 12217035
ca. RAL 9005 tiefschwarz	ltem No. 12219005
ca. RAL 9010 pure white	ltem No. 12219010

Special colors:

Other RAL tones on request Item-No. 12219999

Required dilution for WS-Korrogrund[®] MIX: **WS-Plack**® Dilution MV 751see page 16 Resin dilution KV 657see page 39



WS-Primer M 4021

sand yellow

Low solvent thickfilm high solid zinc phosphate primer (medium solid). Especially for the overcoating with WS-Plast® Thickfilm. Recoatable with all standard one-component, solvent-based coating systems. Compatibility has to be tested by a trial coating. Does not stick on hot galvanized ground. Electrostaticly adjusted. Sand yellow.

Container size:	
750 ml	Item No. 12114021
2,51	
11 kg	Item No. 12314021
30 kg	Item No. 12414021

<u>Required dilution:</u> **WS-Playt**® Dilution MV 751see page 16



WS-Alu Contact Paint AK 7900

shiny

WS-Alu Contact Paint AK 7900 is conductive and protects against corrosion. Strong UV exposure can cause hue changes. WS-Alu-contact-color AK 7900 does not affect the electrical resistance during arc and inert gas welding. WS-Alu Contact Paint AK 7900 is suitable for steel sheets and pipes exposed to heat up to 400° C.

Container size:

2,51	Item No.	16117900
10 I	Item No.	16217900



2-K Basecoats



WS-Epoxy Primer E 2030

sand yellow

2-K thick-layer primer, zinc phosphate containing, based on epoxy resin. Suitable as 2-component zinc primer. Made in accordance with TL / TP KOR 687.02. Electrostatic adjusted.

Mixing ratio: 5 : 1 by weight with specified hardener.

Container size:	Required combinations:
5 kg Item No. 12112030	WS-Epoxid-Hardener EH 203 see page 38
10 kg Item No. 12212030	WS-Epoxid-Dilution EV 250 see page 39

WS-Epoxy-Zinc Durt Primer E 2021

grey

Highly pigmented zinc dust primer based on epoxy resin. Conforms to TL/TP-KOR 687.03. Suitable for highest loads in heavy corrosion protection.

Mixing ratio: 10 : 1 by weight with specified hardener.

Container size:	
10 kg	Item No. 12112021

Required combinations:	
WS-Epoxy-Hardener EH 202	see page 38
WS-Enoxid-Dilution EV 250	see nage 39

WS-PUR-Acryl-Primer U | | 00

grey green

2-component pure acrylate anticorrosive primer, zinc phosphate containing for overcoating with PUR-ACRYL topcoats. Good adhesion to non-anodized aluminum. Electrostatically adjusted.

Mixing ratio: 10 : 1 by weight with specified hardener.

Container size:	
5 kg	Item No. 12111100
10 kg	Item No. 12211100

Required combinations:	
WS-PUR-Acryl Hardener UH 104 see page 38	3
WS-PUR-Dilution UV 150 see page 40)



MAS

WS 4+ I HS Acrylfiller

oxid yellow

Chromate-free, high-solid (MS-quality) 2-component acrylic filler based on polyurethane. Equally well suited for machine and apparatus construction. Pleasantly slightly wet and dry sandable.

Mixing ratio: 4 : 1 by weight with specified hardener.

Container size:

4 I Item No. 12115003

Required hardener: Hardener H 10 short see page 38







I-K Topcoats



WS-CorroXXan K 3707

satin glossy

Corrosion protection and topcoat in one. Quick-drying, well-covering synthetic resin machine paint, with active corrosion protection, ideally suited for the overhauling of production machines, transport racks, oversea containers, crane systems or steel structures. Can be processed without anti-rust primer. Electrostatically adjustable if requested.

Container size:

2,51	. Item No.	. 1311707x
51		
11 kg		
30 kg	. Item No.	. 1341707x

WS-Super-Varnish 3701

high glossy_

Resin-machine paint, top quality, impact-resistant, for high-glossy, weather-resistant and durable coatings exterior and interior, for metal and wood, heat-resistant up to 140° C, for painting, spraying or rolling. Not electrostatically adjustable. Miscible according to RAL and NCS.

Container size:

2,5 1	ltem No. 1311701x
51	Item No. 1321701x
11 kg	
30 kg	
00 kg	

WS-Machine-Paint K 3702

glossy

Fast-drying and well-covering synthetic resin machine paint, scratch-resistant and productive. Not electrostatically adjustable. Miscible according to RAL and NCS.

Container size:	
2,5	. Item No. 1311702x
51	
11 kg	Item No. 1331702x
30 kg	

WS-Machine-Paint K 3710

silkmat

Fast-drying and well-covering synthetic resin machine paint, scratch-resistant and productive. Not electrostatically adjustable. Miscible according to RAL and NCS.

2,51	Item No. 1311710x
51	
11 kg	
30 kg	

Required dilution for above-mentioned paints:

WS-Resin dilution KV 657	see page 39
WS-Fast hardener dilution KV 500	see page 40
WS-Plart® dilution MV 751	see page 16









WS-Super-Metallic-Paint K 3704

glossy_

Synthetic resin machine paint in metallic colors. Top quality, impact-resistant, for durable, weather-resistant coatings on metal and wood, predominantly outdoors. Not electrostatically adjustable.

Container size: 2,5 l	
RAL 9006 white aluminum	Item No. 13113704
RAL 9006 white aluminum RAL 9007 grey aluminum	Item No. 13113704
Container size: 5 l	
RAL 9006 white aluminum	Item No. 13213704
RAL 9006 white aluminum RAL 9007 grey aluminum	Item No. 13213704
Container size: 11 kg	
RAL 9006 white aluminum	Item No. 13313704
RAL 9006 white aluminum RAL 9007 grey aluminum	Item No. 13313704
Container size: 30 kg	
RAL 9006 white aluminum	Item No. 13413704
RAL 9007 grey aluminum	Item No. 13413704



WS-Acryl-Paint

glossy, satin gloss, silkmat or mat

1-component, both indoors	solvent-based, and outdoors.		fast-drying after 30	acrylic minutes.	high-quality lectrostatically	finishes adjusted.
251	US-Acrylic-Paint 4	• •			 Item No Item No Item No Item No). 1311411x). 1321411x). 1331411x
Container size U 2,5 I	US-Acrylic-Paint 4	120 – satin glo	SS		 Item No). 1311412x). 1321412x

Container size **WS-Acrylic-Paint 4140** – silky mat

	(
5 I Item No. 1321414	ł
11 kgItem No. 1331414	ζ
30 kg Item No. 13414143	ł

Container size WS-Acrylic-Point 4180 - mat

2,51	Item No. 1311418x
51	
•	
11 kg	
30 kg	Item No. 1341418x

<u>Required dilution:</u> WS-PUR-Dilution UV 150 see page 40



WS-Zapon-Varnish

high glossy

Non-yellowing high-solid acrylic clearcoat for metals and non-ferrous metals. Prevents the adhesion of patina on copper or the blackening of aluminum sheets. Also sticks on polished stainless steel parts, which are installed in non-exposed places.

Container size:

2,5 I Item No. 16135004

WS-SILAN-Topcoat 4640

black, silkmat

WS-Silan-Topcoat 4640 is used for all temperature-stressed parts in the areas of: Mechanical engineering, equipment construction, plant engineering, in the domestic area for barbecues, fireplaces, ovens or similar (no food authenticity). WS-Silan-Topcoat 4640 is a silicone resin stoving lacquer for steel and metal surfaces with temperature loads up to max. 800° C. The final fully hardness is reached after heating for the first time to at least 180° C. WS-Silan-Topcoat 4640 is moderately grippfast, light chalking is possible.

Container size:	
2,51	. Item No. 13114640
 10 kg	. Item No. 13214640

WS-Chloringted Rubber-Varnish M 4400

satin gloss

Special coating for underwater coating of mineral substrates (swimming pools, ponds, wells, etc.) as well as chemical protection paint against diluted acids and alkalis, also on appropriately primed steel.

Container size: 12,5 kg light blue, sea green, white	. Item No.16214400
Container size: 5 kg Miscible according to RAL and NCS	. Item No.16114400
<u>Required dilution:</u> WS-Nitro-Universal-Dilution ZV 559	see page 39

WS-Iron-Mica-Paint K 3920

satin gloss

Iron mica paint based on long oil alkyd resin for brushing, conventional or airless spraying in the area of heavy corrosion protection of steel parts according to TL/TP KOR-steel structures.

Container size: 12,5 kg	
DB 701 silver grey	Item No. 3110701
DB 702 grey	
DB 703 grey	Item No. 3110703
Required dilution: WS-Resin Dilution KV 657	
	in the page of









2-K Topcoats



WS-PUR-Acryl-Smooth-Finizh

glossy, satin gloss or silkmat

2-component pure polyurethane acrylic paint for high-quality finish painting. Good weather, chemical and color resistance. Electrostatically adjusted.Miscible according to RAL and NCS.

Container size WS-PUR-Acryl-Smooth-Finizh 2000 – glossy	
5 kg	Item No. 1411000x
10 kg	

Gebindegrößen WS-PUR-Acryl-Smooth-Fini/h 2200 – satin gloss	
5 kg	Item No. 1411200x
10 kg	Item No. 1421200x

Gebindegrößen WS-PUR-Acryl-Smooth-Finish 2400 - silky mat

5 kg	. Item No. 1411400x
10 kg	Item No. 1421400x

Mixing ratio: 5 : 1 by weight with specified hardener.

Required combinations:	
WS-PUR-Acrylic-Hardener H 25	see page 38
WS-PUR-Dilution UV 150	see page 40



WS-PUR-Acryl-Smooth-Finizh U 1275

silky mat

2-component PUR iron mica pure acrylic lacquer for high-quality finishes and as top coat in the EG system. Good weather, chemical and color resistance. Electrostatically adjusted.

Container size: 10 kg	
DB 501 blue	Item No. 14111501
DB 502 blue	Item No. 14111502
DB 601 green	Item No. 14111602
DB 602 green	
DB 701 silver grey	
DB 702 grey	
DB 703 grey	
DB 704 grey	
0003 graphite	
0008 black mica	
0010 radiant glimmer	

Mixing ratio: 10: 1 by weight with specified hardener.

Required combinations:

WS-PUR-Acrylic-Hardener UH 175	see page 38
WS-PUR-Dilution UV 150	. see page 40



WS-PUR-Acryl-Textured-Paint 2001

satin glossy_

WS-PUR-Acrylic-Textured-Paint 2001 is a fast-drying 2-component polyurethane acrylic paint for the industrial coating of machines, components, containers, steel structures, agricultural machinery and construction vehicles for painting, rolling or spraying. WS-PUR-Acrylic Textured Paint 2001 results in a pore-tight, structured surface that is hard elastic, mechanically and chemically resistant. It is suitable for a highquality, scratch-resistant, semi-glossy finish coating on metallic surfaces indoors and outdoors.

Mixing ratio: 5 : 1 by weight with specified hardener.

Container size:	
5 kg	Item No. 1411001x
10 kg	Item No. 1421001x
Required combinations:	
WS-PUR-Acrylic Hardener A 61	
WS-PUR-Dilution UV 150	

WS-PUR-Acryl-Bruzh-Paint 2201

satin gloss ____

2-component pure polyurethane acrylic paint for painting and rolling. PUR-Acrylic-Brush Paint 2201 is a high-quality coating mainly used as final coating in the 2-component EG system. Exceptional weathering, chemical and color resistance.

Mixing ratio: 10: 1 by weight with specified hardener.

Container size: 5 kg Item No. 1411022x Required combinations:

WS-PUR-Acrylic-Hardener A 61	. see page 38
WS-PUR-Dilution UV 150	see page 40

WS-PUR-Acryl-Professional 2010

high gloss

High-glossy, 2-component, machine paint for highest demands and weather resistance. Extremely scratch and impact resistant, air drying and oven drying at 80° C. Available in all RAL colors acc. color chart table and house shades of machine and commercial vehicle manufacturers. Electrostatically adjusted.

Mixing ratio: 3 : 1 by weight with specified hardener.

Container size: 3 kg	Item No. 1421010x
6 kg	Item No. 1411010x
Required combinations:	
Required combinations: WS-PUR-Acrylic-Hardener H 25 WS-PUR-Dilution UV 150	see page 38







WS-Ероху-Торсоаt Е 2220 HS

glossy

2-component epoxy resin topcoat in high-solid quality, low solvent content. Fullfills all EG regulations (e.g., VOC) for solvent reduction beyond 2010. Particularly strong mechanical and chemical claims. Electrostatically adjusted.

Mixing ratio: 6 : 1 by weight with specified hardener.

Container size:	
6 kg	Item No. 14112220

Required	combinations:
noquirou	oomsmattono.

WS-Epoxid-Hardener EH 201	see page 38
WS-Epoxid-Dilution EV 250	see page 39





WS-Εροχy-Τοροσαι Ε 220 Ι

glossy

Iron mica topcoat based on epoxy according to DB specification. As a 2-component primer on hot-dip galvanized surfaces or as intermediate coat in heavy corrosion protection. Electrostatically adjusted.

Mixing ratio: 5 : 1 by weight with specified hardener.

Container size: 10 kg Item No. 14112201

Required combinations:	
WS-Epoxid-Hardener EH 204	see page 38
WS-Epoxid-Dilution EV 250	see page 39

Cleaners & Maintenance Products



WS-Rust-Remover-fluid

Due to its extraordinary creeping ability, this fluid dissolves stuck and corroded connections of screws, bolts, locks and hinges. Further rusting is prevented. The simultaneous lubricating effect prevents creaking and squeaking.

Container size: 5 I Item-No. 17863050



WS-150-Cold Degreazer

quickly fleeing

WS-150 Cold Degreaser is a cleaner for oily and greasy sheets, profiles, rubber, light metal and plastic parts. WS-150-Cold Degreaser is perfect for preparing surfaces which have to be painted. Also removes mold release agents. WS-150-Cold Degreaser is very suitable for cleaning devices of small parts.

Container size: 5 I Item-No. 17851550



WS-160-Cold Degreaser

slowly fleeing ____

Gentle cleaning agent based on low-aromatic solvents with a high flash point. Perfect for cleaning applications in precision mechanics and electronics.

Container size: 5 I Item-No. 17851650



WS-Silicone-Fluid

Film-forming lubricants. Protects and impregnates plastic, rubber and textile fabrics. Anti-adhesive.

Container size: 5 I Item-No. 17865050



WS-40-Multifunction-Fluid

Multifunctional fluid with many functions such as: Stops squeaking and creaking, protects against corrosion in precision engineering, protects against the freezing of door locks, door rubbers and antennas, creeps and displaces moisture, acts antistatic, for electronic systems, dries wet ignition systems and eliminates startup problems. Silicone free.

Container size: 5 I Item-No. 17860050



WS-Stainless Steel Care Fluid

WS-Stainless Steel Cleaning Fluid cleans and cares for matt and polished stainless steel surfaces. Contaminants such as grease, oil and finger marks are easier to remove. It leaves a wafer-thin care film that counteracts repolluting.

Container size: 5 I Item-No. 17863850



WS-All-Purpose-Cleaner

slightly alkaline

Concentrate for cleaning heavy and difficult to remove soiling. Cleans machines, engines, vehicles and plant equipment. Can be used in almost all cleaning and degreasing cases in trade and industry. Acid-free, non-toxic, not harmful to health, biodegradable. Can be used for manual cleaning, in high-pressure cleaner and spray extraction device.

Container size:

5 I Item-No. 17830050

Registered with the Federal Environmental Agency under UBA No. 1258 0010

WS-Power-Cleaner CPE 150

Self-acting cleaning concentrate. Degreases metals, dissolves resinified fats, oils, soot and nicotine deposits. Cleans even the most persistant dirt during post-fire restaurantion etc. The professional cleaning concentrate for hand cleaning and high-pressure cleaners. Biodegradable.

Container size:	
51	Item-No. 17832050

Registered with the Federal Environmental Agency under UBA No. 1258 0011

WS-Metal-Cleaner

sour

WS-Metal-Cleaner is a highly concentrated cleaner for mineral soiling such as lime, cement veil, rust, etc. Suitable for the cleaning of iron, nonferrous metals and anodized surfaces. WS-Metal-Cleaner is ideally suited as a highly effective rim cleaner for aluminum and steel rims. WS-Metal-Cleaner removes soot and brake dust.

Container size: 5 I Item-No. 17820050

Registered with the Federal Environmental Agency under UBA No. 1258 0012






Dilutions & Hardener



WS-PUR-Acryl Hardener

Hardener H 10 short for WS-PUR-Acryl-Filler 1 kg	. Item-No. 19115210
Hardener H 25 for WS-PUR-Acryl-Topcoats 1 kg	. ltem-No. 19115225
Hardener A 61 for WS-PUR-Acryl-Texture- or Brush- Pa	int
1 kg	. Item-No. 19115260
0,5 kg	
Hardener UH 104 für WS-PUR-Acryl-Primer	
0,5 kg	. Item-No. 19110104
1 kg	. Item-No. 19210104
Hardener UH 175 for WS-PUR-Acryl U 1275	
1 kg	. Item-No. 19110175



WS-Epoxy-Hardener

Hardener EH 201 for WS-Epoxy E 2220 1 kg	Item-No. 19110201
Hardener EH 202 for WS-Epoxy E 2021 1 kg	Item-No. 19110202
Hardener EH 203 for WS-Epoxy E 2030 1 kg 2 kg	
Hardener EH 204 for WS-Epoxy E 2201 1 kg	Item-No. 19110204



WS-Rezin-Dilution KV 657

For thinning WS-Korrogrund $^{\ensuremath{\texttt{B}}}$ und synthetic resin topcoats.

Container sizes:	
51	Item-No. 18210657
10 I	Item-No. 18310657
30	Item-No. 18410657



WS-Nitro-Universal-Dilution ZV 559

For thinning WS-Zink® 80/81, WS-Zink® A 6005 and Nitro paints.

Container sizes:

51	Item-No. 18110559
10	Item-No. 18210559
30	Item-No. 18310559



WS-Epoxy-Dilution EV 250

For thinning epoxy primers and topcoats.

Container sizes:	
1000 ml	Item-No. 18110250
51	Item-No. 18210250
10	Item-No. 18310250
30	Item-No. 18410250



WS-Washing-Dilution RV 895

Mild odor, good cleaning

Container sizes:

51	Item-No. 18110895
10	Item-No. 18210895
30	Item-No. 18310895



WS-fasthardener-Dilution KV 500

For thinning synthetic resin paints, at the same time accelerates the drying and hardening of the paints.

Container size: 1000 ml Item-No. 18110500



WS-PUR Dilution UV 150

For thinninh WS-PUR-Acryl primers and topcoats.

Container sizes:

1000 ml	Item-No. 18110150
51	Item-No. 18210150
10	Item-No. 18310150
30	Item-No. 18410150







Industrial ring brushes

Bright bristle, wooden handle, plastic bandage. Delivery only in boxes of 12 pieces. Various sizes:

Size 4	= approx. 25 mm	Item-No. 98610044
Size 6	= approx. 30 mm	Item-No. 98610144
Size 8	= approx. 35 mm	Item-No. 98610244
Size 10	= approx. 40 mm	Item-No. 98610344
Size 12		Item-No. 98610444



Paint brushes

Pure black China bristle, wooden handle, metal bandage. Delivery only in boxes of 12 pieces. Various sizes:

Width 1,0" = approx. 25 mm	Item-No. 98611044
Width 1,5" = approx. 40 mm	Item-No. 98611144
Width 2,0" = approx. 50 mm	Item-No. 98611244
Width 2,5" = approx. 60 mm	



Radiator-bruzh

Bright bristle, wooden handle - about 40 cm long, metal-bandage. Delivery only in boxes of 12 pieces. Various sizes:

Width 1,0" = approx. 25 mm	Item-No. 98630044
Width 1,5" = approx. 40 mm	Item-No. 98630144
Width 2,0" = approx. 50 mm	
Width 2,5" = approx. 60 mm	



flat brush

Bright, metal-filled bristle, screwable plastic handle, metal-bandage. Container clamping device. Delivery only in boxes of 12 pieces.

Size 12 x 3 cm Item-No. 98620044



Paint roller

Width: 10 cm.

Short velor 4 mm paint rollers	. Item-No. 98650444
Moltopren (foam) paint rollers	
Perlon Velor Premium painting rollers	. Item-No. 98650344

Delivery only in pack of 10 pieces.



Paint roller hanhdle

For holding 10 cm paint rollers. Metal shaft, plastic handle.

44 cm Item-No. 98650044



Paint tray

Solvent-resistant plastic tray with scraper surface.

18 x 30 cm Item-No. 98682444



Viscosity measuring cup

Aluminum, extruded DIN 4 mm	Item-No. 98682544
Plastic DIN 6 mm	Hom No 00002044



3M Standard paint mark ret 6000

Contents: mask body, 2 x filter A2, 4 x filter P3, 2 x filter housing cover, 10 x cleaning cloth, 1 x storage box

Size M or L Item-No. 98671044





3M Premium paint mark ret 7500

Content: Premium mask body, 2 x filter A2, 4 x filter P3, 2 x filter housing cover, 10 x cleaning cloth, 1 x storage box

Size M or L Item-No. 98671144

3M replacement

further 3M products on request



for water-based cleaners and care products

Plastic bottle 1000 ml with hand spray head

...... Item-No. 99061044

Ουρ ουη

We carry various models from different manufacturers. Different designs and nozzle sizes on request! Fine atomization with high area performance. Optimal work results in all application areas. Highly flexible spray pressure setting.

Zinc file*s*

Special files to plaster hot dip galvanized parts. Zinc noses, zinc picks and slag inclusions can easily be rasped away without the files becoming clogged and the galvanizing parts getting damaged. Shortens the working time when plastering by about 50%. All files with mounted shaft!

Zinc file, shallow point, 1 round edge, special cut 250 x 25 x 6 mm Item-No. 98681744

Zinc file, convex curved (zinc plane), special cut 190 x 25 x 5,5 mm Item-No. 98681644

Zinc file, flat, milled, 13 teeth per inch 300 x 29 x 6,5 mm Item-No. 98681844





ITW-Ranzburg No. 2®

We are an authorized dealer for the complete range of replacement parts for the named electrostatic spraying systems. Please contact us!

The electrostatic hand spray gun no. 2[®] is named for particularly fine atomization and nearly 100% paint yield.

Efficiency, environmental friendliness and high quality are its main features. Instead of a nozzle, it is equipped with an air-driven, rotating spray bell and works with ultrafine, purely electrostatic atomization. With a paint yield of almost 100%, the No.2 achieves unsurpassed paint savings. This makes it the ideal tool for economical painting - especially for filigree parts. At the same time, the No.2 provides a significant reduction in solvent emissions and significantly reduced user exposure.

Typical applications:

- » Fence, lattice, railing production
- » Blacksmith
- » Fine arts (jewelery and watch industry)
- » Wire products
- » "One-site" office furniture renovation
- » Security doors and fittings
- » Amusement park and playground equipment

..... Item-No. 98607745



We also offer the following:

- » Steel fire coating systems
- » Water-based paints
- » Our products in your label (paints and aerosols)
- » Aerosols in contract filling

Just contact us!





W+S GmbH Lackchemie und Aerosol-Technik

Am Sportplatz 5 63791 Karlstein Deutschland

Contact:	
Phone	+49 (0) 6188 9575 — 0
Fax	+49 (0) 6188 9575 — 30
Mail:	info@ws-lackchemie.de
Web:	www.ws-lackchemie.de

Opening hours:		
Mo-Do:	07:30 - 16:30 Uhr	
Fr:	07:30 - 16:00 Uhr	



W+S GmbH Lackchemie und Aerosol-Technik